



## KeHong Enterprises Co.,Ltd.

No,7118,Floor 7, Sha Feng Business Building, Jin sha zhou, Baiyun Guangzhou, China

www.khenterprise.en.alibaba.com, Tel:+86-20-82586869,Mobile:+8615918777767

Email: lily@gzhelectric.com

---

### Perfect non slip heat shrink tube

#### Feature:

Skid proof flower lined heat shrink tubing is made of high-polymer with scientific formula, via advanced technology processing. It has the advantage of environment friendly, good flexibility, skidproof, perfect appearance, fast shrinkage, and stable performance.

#### Application range:

Functional usage: Widely used in fishing and sports.

fishing tackles, sports fittings, health equipment and commodities, etc.

1. Shrink ratio:2:1
2. Shrinking temperature: Start at 70°C, and full recovery at 110°C
3. Operating temperature: -55°C~105°C
4. Soft, non-slip, perfect appearance, fast shrinkage and stable performance.

#### Product Size:

Size(mm)	As supplied(mm)		After recovery(mm)		Standard package (M/pcs)
	ID	Average. Wall Thickness.	Max I.D.	Average. Wall Thickness.	
φ15	≥15	0.45±0.15	8	0.85±0.15	1.0
φ20	≥20	0.50±0.15	11	0.90±0.15	0.8/1.0/1.6
φ22	≥22	0.50±0.15	12.5	0.90±0.15	0.8/1.0/1.6
φ25	≥25	0.50±0.15	14.5	1.00±0.15	0.8/1.0/1.6
φ28	≥28	0.50±0.15	15.5	1.00±0.15	0.8/1.0/1.6
φ30	≥30	0.60±0.15	17.5	1.20±0.15	0.8/1.0/1.6
φ35	≥35	0.60±0.15	20.0	1.20±0.15	0.8/1.0/1.6
φ40	≥40	0.60±0.15	23.0	1.20±0.15	0.8/1.0/1.6
φ45	≥45	0.65±0.15	25.0	1.25±0.15	0.8/1.0/1.6
φ50	≥50	0.65±0.15	28.0	1.25±0.15	0.8/1.0/1.6